

AMENDMENTS TO THE CLAIMS

1. (currently amended) A device for attaching to a water structure for producing an artificial waterfall, the device comprising:

a. an elongated member comprising a first interior chamber, a second interior chamber, a feed water inlet into the first interior chamber, a distribution slot fluidly connecting the first interior chamber to the second interior chamber, and a waterfall slot; and

b. a first end piece fluidly connected to a water source and fluidly connected to the elongated member for allowing feed water to flow from the water source through the feed water inlet into the elongated member,

wherein the first end piece and a second end piece comprise attachment means for securing the elongated member to the water structure, and

wherein the first end piece and the second end piece ~~are structured to hold~~ the elongated member at a distance from the water structure and above the surface of the water in the water structure so that the ~~device-elongated member~~ functions as a handle for a user of the water structure.

2. (original) The device as claimed in Claim 1, wherein the first chamber and the second chamber are separated from each other by a divider and wherein the distribution slot delineates a passageway through the divider allowing fluid communication between the first chamber and the second chamber.

3. (original) The device as claimed in Claim 1, wherein the waterfall is produced from water flowing from the waterfall slot.

4. (cancelled).

5. (previously presented) The device as claimed in Claim 1, wherein the water structure is an artificial body of water.

6. (currently amended) The device as claimed in Claim 5, wherein the water structure is selected from the group consisting of spas, swimming pools, and tubs ~~and showers, and the water source is a water filtering system used with the supporting structure.~~

7. (cancelled).

8. (cancelled).

9. (previously presented) A device for attaching to and producing an artificial waterfall in an artificial water structure, the device comprising:

a. an elongated member comprising a first interior chamber, a second interior chamber, a feed water inlet into the first interior chamber, a distribution slot fluidly connection the first interior chamber to the second interior chamber, a divider separating the first chamber and the second chamber from each other, and a waterfall slot;

b. a first end piece fluidly connected to a water source and fluidly connected to the elongated member for allowing feed water to flow from the water source through the feed water inlet into the elongated member and comprising attachment means for securing the elongated member to the artificial water structure; and

c. a second end piece also comprising attachment means for securing the elongated member to the artificial water structure,

wherein the distribution slot delineates a passageway through the divider allowing fluid communication between the first chamber and the second chamber, the first end piece and the second end piece are attached to opposite ends of the elongated member, and the waterfall is generated from the water flowing to the water structure, and

wherein the elongated member is rotatable within the first end piece and the second end piece and the rotation of the elongated member varies the direction of the waterfall,

whereby passage of the water from the first chamber to the second chamber through the divider more evenly distributes the water within the elongated member so as to create a more uniform waterfall.

10. (original) The device as claimed in Claim 9, wherein the elongated member, the first end piece, and second end piece form a continuous structure.
11. (original) The device as claimed in Claim 9, wherein the water entering the elongated member exits exclusively out of the waterfall slot.
12. (original) The device as claimed in Claim 9, wherein the first chamber transiently collects the water and transfers the water through the distributing slot to the second chamber, and the second chamber channels the water to and through the waterfall slot.
13. (original) The device as claimed in Claim 12, wherein the waterfall has a sheet-like shape.
14. (previously presented) The device as claimed in Claim 9, wherein the artificial water structure is an artificial body of water.
15. (currently amended) The device as claimed in Claim 14, wherein the artificial water structure is selected from the group consisting of spas, swimming pools, and tubs, ~~and showers, and the water source is a water filtering system used with the supporting structure~~
16. (cancelled).

17. (currently amended) A device for attaching to and producing an artificial waterfall in an artificial water structure, the device comprising:

a. an elongated member comprising a first interior chamber, a second interior chamber, a feed water inlet into the first interior chamber, a distribution slot fluidly connection the first interior chamber to the second interior chamber, a divider separating the first chamber and the second chamber from each other, and a waterfall slot;

b. a first end piece fluidly connected to a water source and fluidly connected to the elongated member for allowing feed water to flow from the water source through the feed water inlet into the elongated member and comprising attachment means for securing the elongated member to the water structure; and

c. a second end piece also comprising attachment means for securing the elongated member to the water structure,

wherein the distribution slot delineates a passageway through the divider allowing fluid communication between the first chamber and the second chamber, the first end piece and the second end piece are attached to opposite ends of the elongated member, and the waterfall is generated from the water flowing to the water structure,

wherein the first end piece comprises a channel therethrough for fluidly connecting the water source to the first chamber through the feed water inlet, and

wherein the first end piece and the second end piece ~~are structured to hold~~ the elongated member at a distance from the water structure and above the surface of the water in the water structure so that the ~~device-elongated member~~ functions as a handle for a user of the water structure,

whereby passage of the water from the first chamber to the second chamber through the divider more evenly distributes the water within the elongated member so as to create a more uniform waterfall.

18. (cancelled).

19. (currently amended) A device for attaching to and producing an artificial waterfall in an artificial water structure, the device comprising:

- a. an elongated member comprising a first interior chamber, a second interior chamber, a feed water inlet into the first interior chamber, a distribution slot fluidly connection the first interior chamber to the second interior chamber, a divider separating the first chamber and the second chamber from each other, and a waterfall slot;
- b. a first end piece fluidly connected to a water source and fluidly connected to the elongated member for allowing feed water to flow from the water source through the feed water inlet into the elongated member and comprising attachment means for securing the elongated member to the water structure; and
- c. a second end piece also comprising attachment means for securing the elongated member to the water structure,

wherein the first end piece and the second end piece ~~are structured to hold~~ the elongated member at a distance from the water structure and above the surface of the water in the water structure so that the device ~~elongated member~~ functions as a handle for a user of the water structure.

20. (currently amended) The device as claimed in Claim 19, wherein the first end piece is connected to a source of water, the first end piece and the second end piece are attached to opposite ends of the elongated member ~~through the attachment means~~, and at least the first end piece ~~has an internal structure to channel~~ channels the water flow from the source of water into the first chamber.

21. (original) The device as claimed in Claim 20, wherein the divider and the distribution slot cooperate whereby passage of the water from the first chamber to the second chamber through the divider more evenly distributes the water within the elongated member so as to create a more uniform waterfall, and the device further functions as a handle for a water structure.

22. (original) The device as claimed in Claim 21, wherein the waterfall slot extends lengthwise across the majority of the length of the elongated member.
23. (original) The device as claimed in Claim 21, wherein the water entering the elongated member exits exclusively out of the waterfall slot.
24. (original) The device as claimed in Claim 21, wherein the elongated member is rotatable within the first end piece and the second end piece and the rotation of the elongated member varies the direction of the waterfall.
25. (original) The device as claimed in Claim 21, wherein the first end piece comprises a channel therethrough for fluidly connecting the water source to the first chamber through the feed water inlet.
26. (original) The device as claimed in Claim 25, wherein the first chamber transiently collects the water and transfers the water through the distributing slot to the second chamber, and the second chamber channels the water to and through the waterfall slot.
27. (original) The device as claimed in Claim 21, further comprising a plurality of distribution slots through the divider.
28. (original) The device as claimed in Claim 21, wherein the second end piece is fluidly connected to a water source and is fluidly connected to the elongated member for allowing feed water to flow from the water source through a second feed water inlet into the elongated member.
29. (original) The device as claimed in Claim 28, wherein the second end piece comprises a channel therethrough for fluidly connecting the water source to the first chamber through the second feed water inlet.
30. (original) The device as claimed in Claim 21 in combination with a spa.

31. (previously presented) The device as claimed in Claim 1, wherein the first chamber transiently collects the feed water and transfers the water through the distributing slot to the second chamber, and the second chamber channels the water to and through the waterfall slot.

32. (previously presented) The device as claimed in Claim 31, wherein the first end piece comprises a channel therethrough for fluidly connecting the water source to the first chamber through the feed water inlet.

33. (currently amended) The device as claimed in Claim 9, wherein the first end piece and the second end piece ~~are structured to hold~~ the elongated member at a distance from the water structure so that there is a space between the elongated member and the water structure and the ~~device~~ elongated member functions as a handle for a user of the water structure.